

SH10-150 HEAVY DUTY SUBMERSIBLE SLURRY PUMP WITH AGITATOR



CIRCLE PUMPS CO., LTD No. 2-2, Hsin Hsing Rd, Peitun. Taichung. Taiwan R.O.C Tel : +886 4 24264898 Fax : +886 4 24256230

- 333cc HYDRAULIC PISTON MOTOR.
- DISCHARGE SIZE 10 INCH (250MM).
- HIGH PRESSURE MECHANICAL SEAL.
- DESIGNED FOR HEAVY SAND SLURRIES.
- HYDRAULIC OR ELECTRIC DRIVE.
- JETTING RING ATTACHMENT OPTIONS.


High Capacity 12m³/min At 15m Head (100HP)

Excellent combination of heavy duty wear resistant materials, variable input drive power with wide enclosed impeller provides high flow capacities with sufficient power to pump heavy slurries, sands and gravels.

Our special high pressure double mechanical seal provides excellent integrity at deeper water depths.

Oil filled bearing housing for deep water applications.

SH10-150



The main features of our heavy duty slurry pump is a heavy design of wear resistant casing and 28% HiCr impeller. Excellent combination of materials provides long term operation even in harsh abrasive slurries.

Incorporating high pressure mechanical seal in double TC

Optional Accessories

Diesel or Electric Driven Hydraulic Power Pack.

Umbilical Power Spooler.

Heavy duty rubber delivery hoses, HDPE hoses, Floating Pipes.

Jetting water nozzle attachments, jetting pumps, hoses.

Lifting frame Options, excavator mounting plates.