

DIESEL ENGINE DRIVEN HYDRAULIC POWER PACK

SPECIFICATIONS MODEL SPP-300

DESCRIPTION	DIESEL DRIVEN HYDRAULIC POWER PACK 350 Ltr/min at 240 BAR
ENGINE	MITSUBISHI 6D24T 250HP AT 1800 RPM
HYD. PUMP	DIRECT DRIVE HYDRAULIC PUMP
ELECTRICS	24VDC CONTROL SYSTEM PC BOARD SAFETY SHUT DOWN
HYD. FILTERS	SUCTION / HP PRESS / RETURN LINE FILTERS
HYD. CONTROL	MANIFOLD WITH RELIEF / BYPASS / CHECK VALVES / 24V SPOOL VALVE
HYD. TANK	800 LTR WITH FILLER BREATHER
HYD. CONNECT.	1-1/2" SUPPLY / RETURN + 1" DRAIN LINE
OIL COOLER	COOLING THROUGH ALUMINIUM RADIATOR BY ENGINE FAN
DIMENSION	400cm x 150cm x 200cm (APPROX)
WEIGHT	3200kgs (NET)



Note : Specifications subject to change according to final project specification design.

Manufacture, Sales and Distribution of Contractor Pumps & Dredging Equipment.